

Beodric House, 5 Boldero Road Bury St. Edmunds Suffolk. IP32 7BS

Tel: 01767 677445 admin@chaucersolutions.co.uk www.chaucersolutions.co.uk

SAFETY DATA SHEET

(according to Regulation (EC) No. 1907/2006) Version: 1 Revision Date: 25.08.2020

METHYLATED SPIRITS 5 LITRES

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name: Product Code: REACH Registration Number: Methylated Spirits 5 Litres METHS05 All components / constituent materials used in this product have been registered under REACH where required.

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company:CHAUCER SOLUTIONS LIMITEDAddress:Beodric House5 Boldero RoadBury St. EdmundsSuffolkIP32 7BSUnited KingdomUnited KingdomTelephone:+ 44 (0) 1767 677445E-mail:admin@chaucersolutions.co.uk

1.4 Emergency telephone number

+ 44 (0) 1767 677445 (Only available during office hours)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (according to Regulation (EC) No. 1272/2008):

Flammable Liquid Category 2 Acute Toxicity Category 4 Eye Irritant Category 2 STOT SE Category 2

2.2 Label elements

REGULATION (EC) No. 1272/2008

Pictogram(s):

- H225: Highly flammable liquid and vapour
- H302: Harmful if swallowed
- H319: Causes serious eye irritation
- H371: May cause damage to organs

Page 1 of 9



Beodric House, 5 Boldero Road Bury St. Edmunds Suffolk. IP32 7BS

Tel: 01767 677445 admin@chaucersolutions.co.uk www.chaucersolutions.co.uk

21



DANGER

Signal Word:

Hazard Statements:

Hazard Statem	ents:
	H225: Highly flammable liquid and vapour
	H302: Harmful if swallowed
	H319: Causes serious eye irritation
	H371: May cause damage to organs
Precautionary S	Statements:
Prevention:	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
	P233: Keep container tightly closed
	P243: Take precautionary measures against static discharge
	P260: Do not breathe dust / fumes / gas / mist / vapours / spray
	P264: Wash hands thoroughly after handling
	P270: Do not eat, drink or smoke when using this product
	P271: Use only outdoors or in a well-ventilated area
	P280: Wear protective gloves / protective clothing/eye protection/face protection
Response:	P303+P361+P353:
	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water
	P304+P340:
	IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing
	P305+P351+P338:
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
	easy to do. Continue rinsing
	P312: Call a POISON CENTER / doctor / medical professional / if you feel unwell
	P330: Rinse mouth
	P337+313:
	If eye irritation persists get medical advice/attention
	P370+378:
	In case of fire: Use appropriate fire extinguisher for extinction.
Storage:	P403+233:
	Store in a well-ventilated place. Keep container tightly closed
	P403+235:
	Store in a well-ventilated place. Keep cool
	P405: Store locked up
Disposal:	P501: Dispose of contents / container to a waste management service provider, according to the local law and
	regulations
2.3 Other Ha	azards None known

3. COMPOSITION OF/INFORMATION ABOUT THE COMPONENTS

3.1 Substances



Beodric House, 5 Boldero Road Bury St. Edmunds Suffolk. IP32 7BS

Tel: 01767 677445 admin@chaucersolutions.co.uk www.chaucersolutions.co.uk

3.2 Mixtures

Chemical Name	CAS-No. EINECS-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration [%]
ethyl alcohol (ethanol)	64-17-5 200-578-6 01-2119457610-43-XXXX	Flam. Liq. 2: H225	50 - 100 %
methanol	67-56-1 200-659-6 01-2119433307-44-XXXX	Flam. Liq. 2: H225, Acute Tox. 3: H301, Acute Tox. 3: H311, Acute Tox. 3: H331, STOT SE 1: H370	<i>≤ 3.9 %</i>

For the full text of the H - statements mentioned in this section, see section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice: Take the Hazard and Precautionary Statements (section 2) into account. Show this Safety Data Sheet to the physician in attendance if required.

- Inhalation: *Remove from exposure site to fresh air and keep at rest. Contact physician if symptoms persist.*
- Skin contact: Remove contaminated clothes. Wash thoroughly with water (and soap). Contact physician if symptoms persist. Eye contact: Flush immediately with water for at least 15 minutes. Remove contact lenses if possible. Contact physician if symptoms persist.
- Ingestion: Rinse mouth with water and Contact physician if symptoms persist. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Headache, dizziness, unconsciousness, nausea

4.3 Indication of any immediate medical attention and special treatment needed

Provide physician with a copy of this Safety Data Sheet.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: *Water spray, carbon dioxide, dry chemical, foam.* Extinguishing media which shall not be used for safety reasons: *Do not use a high-powered water jet directly on burning material.*

5.2 Special Hazards arising from the substance or mixture

No information available

5.3 Advice for Fire Fighters

Special protective equipment for fire-fighting: No information available

Specific fire-fighting methods:

Do not use a high-powered water jet directly on burning material. Do not inhale fumes. Evacuate personnel to a safe area. Cool containers / tanks with water spray.

Page 3 of 9



Beodric House, 5 Boldero Road Bury St. Edmunds Suffolk. IP32 7BS

Tel: 01767 677445 admin@chaucersolutions.co.uk www.chaucersolutions.co.uk

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition and keep away from flames and hot surfaces. Avoid inhalation and contact with skin and eyes. Wear appropriate personal protective equipment. A self-contained breathing apparatus is recommended in case of a major spill. Collect Spillage.

6.2 Environmental precautions

Keep away from drains, surface and ground water and soil.

6.3 Methods for cleaning or taking up

Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

7. HANDLING AND STORAGE

7.1 Handling

Advice on safe handling:

Avoid contact with the eyes, skin and clothing. Avoid excessive inhalation of concentrated vapours. Follow good manufacturing practices for housekeeping and personal hygiene. Wash any exposed skin immediately after any

chemical contact, before breaks and meals, and at the end of each working period. Contaminated clothing and shoes should be thoroughly cleaned before re-use.

If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapour concentrations in the work place air. Where chemicals are openly handled, access should be restricted to properly trained employees.

Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.

Advice on protection against fire and explosion:

Keep away from ignition sources and naked flame.

7.2 Storage

Requirements for storage areas and containers:

Store in a cool, dry, ventilated area away from heat sources. Keep containers upright and tightly closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters

Ingredients with limit values that require monitoring at the workplace:

Ethyl alcohol (CAS: 64-17-5):

_____ WEL, long-term value: 1,920 mg/m³, 1,000 ppm

Methanol (CAS: 67-56-1):

- WEL, short-term value: 333 mg/m³, 250 ppm
- WEL, long-term value: 266 mg/m³, 200 ppm

Page 4 of 9



Beodric House, 5 Boldero Road Bury St. Edmunds Suffolk. IP32 7BS

Tel: 01767 677445 admin@chaucersolutions.co.uk www.chaucersolutions.co.uk

8.2 Personal protective equipment

Respiratory protection:

Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation including places where this material is openly weighed or measured.

In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures. No respiratory protection is required during normal operations in a workplace where engineering controls such as adequate ventilation, etc. are sufficient.

If engineering controls and safe work practices are not sufficient, an approved, properly fitted respirator with organic vapor cartridges or canisters and particulate filters should be used:

a) while engineering controls and appropriate safe work practices and/or procedures are being implemented; or b) during short term maintenance procedures when engineering controls are not in normal operation or are not sufficient; or

c) if normal operational workplace vapour concentration in the air is increased due to heat; d) during emergencies; or

e) if engineering controls and operational practices are not sufficient to reduce airborne concentrations below an established occupational exposure limit.

Particle filter class P2SL (EN143). Particle filter class P3SL (EN143).

Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Avoid skin contact. Use chemically resistant gloves, approved to BS EN 374.

Skin and body protection:

Avoid contact with the skin. Wear a protective suit. Wash all contaminated clothing thoroughly before re-use.

Eye protection: Avoid contact with the eyes. Use tight-fitting goggles, face shield or safety glasses with side shields (approved to EN166 standard).

Hygiene Measures:

Ensure that eyewash stations and safety showers are close to the workstation location. Use clean, wellmaintained personal protection equipment. Wash hands before breaks and at the end of the working day. Do not eat, drink or smoke whilst using or handling the product.

To the extent deemed appropriate, implement pre-placement and regularly scheduled ascertainment of symptoms and spirometry testing of lung function for workers who are regularly exposed to this material.

To the extent deemed appropriate, use an experienced air sampling expert to identify and measure volatile chemicals that could be present in the workplace air or determine potential exposures and to ensure the continuing effectiveness of engineering controls and operational practices to minimize exposure.

Protective measures:

The protective equipment must be selected in accordance with current CEN standards and in cooperation with the supplier of the protective equipment. Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the potential hazards and / or risks that may occur during use.

General Advice: Do not allow uncontrolled discharge of the product into the environment.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Appearance

Physical state:	Liquid
Colour:	Colourless to purple



Beodric House, 5 Boldero Road Bury St. Edmunds Suffolk. IP32 7BS

Tel: 01767 677445 admin@chaucersolutions.co.uk www.chaucersolutions.co.uk

Odour: Characteristic, pungent, alcohol

9.2 Safety data

Flash Point:	13°C (as Ethyl Alcohol)
pH:	No data available
Boiling Point:	78°C (as Ethyl Alcohol)
Density g/cm ³ :	0.790 - 0.820 at 20°C
Viscosity:	Non-viscous
Vapour Pressure:	59 hPa at 20°C
Solubility:	Fully miscible in water: 1 g/l

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available.

- **10.2 Chemical Stability** *No data available.*
- **10.3 Possibility of hazardous reactions** No data available.
- **10.4 Conditions to avoid** *No data available.*
- **10.5 Incompatible materials** *No data available.*
- **10.6 Hazardous decomposition products** *No data available.*

11. TOXICOLOGICAL INFORMATION

11.1 Acute Toxicity

Methanol (CAS: 67-56-1):

- Oral LD50: 5,628 mg/kg (rat)
- Dermal LD50: 15,800 mg/kg (rabbit)

11.2 Skin corrosion/irritation

Skin irritation: May cause irritation to the skin.

11.3 Serious eye damage/eye irritation

Eye irritation: Causes serious eye damage.

11.4 Respiratory or skin sensitization

Sensitisation: No data available.

11.5 Aspiration hazard:

Sensitisation: No data available.

11.6 Repeated dose toxicity

Repeated dose toxicity: *No data available.*

Page 6 of 9



11.7 STOT

STOT – single exposure: *May cause damage to organs.*

STOT – repeated exposure: *No data available.*

11.8 Carcinogenicity Carcinogenicity: *No data available.*

11.9 Mutagenicity

Genotoxicity in vitro: *No data available.* Genotoxicity in vivo: *No data available.*

11.10 Reproductive toxicity

Reproductive toxicity: *No data available.* Developmental toxicity/Teratogenicity: *No data available.*

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity effects

Aquatic Compartment (including sediment) No data available.

12.2 Persistence and degradability

Biodegradability: No data available.

12.3 Bioaccumulation

Partition coefficient (n-octanol/water): No data available.

12.4 Mobility

Known distribution to environmental compartments: No data available.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product: Dispose of according to local regulations. Do NOT dispose of into drainage systems and into the environment. Contaminated packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

14.1 ADR	
UN-Number:	1170
Dangerous Goods Description:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
Class:	3
Packing group:	II
Classification Code:	F1

Page 7 of 9

Chaucer Solutions Ltd

Beodric House, 5 Boldero Road Bury St. Edmunds Suffolk. IP32 7BS

Tel: 01767 677445 admin@chaucersolutions.co.uk www.chaucersolutions.co.uk



Beodric House, 5 Boldero Road Bury St. Edmunds Suffolk. IP32 7BS

Tel: 01767 677445 admin@chaucersolutions.co.uk www.chaucersolutions.co.uk

Tunnel restriction code:	(D/E)
Environmentally hazardous mark:	No
Hazard Identification No:	33

14.2 RID

UN-Number:	1170
Dangerous Goods Description:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
Class:	3
Packing group:	II
Classification Code:	F1
Tunnel restriction code:	(E)
Environmentally hazardous mark:	No
Hazard Identification No:	33

14.3 IATA

UN-Number:	1170
Dangerous Goods Description:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
Class:	3
Packing group:	П
Environmentally hazardous mark:	No
PCA Excepted quantities:	E2
PCA limited quantity max net quant	tity:
	1L

14.4 IMDG

UN-Number:	1170		
Dangerous Goods Description:	ETHANOL SOLUTIO	N (ETHYL ALCOHOL	SOLUTION)
Class:	3		
Packing group:	II		
Environmentally hazardous mark:	No		
Excepted quantities:	E2		
EmS Code:	F-E, S-D		

14.5 ADN / ADNR

UN-Number:	1170
Dangerous Goods Description:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION
Class:	3
Packing group:	Π
Environmentally hazardous mark:	No

Note: The above regulatory prescriptions are those valid on the date of publication of this sheet. Given the possible evolution of transport regulations for hazardous materials, it would be advisable to regularly check their validity.

15. REGULATORY INFORMATION

National regulations:

EU legislation:

Control of Substances Hazardous to Health Regulations 2002 (as amended). Health and Safety at Work etc. Act 1974 (as amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Page 8 of 9



Beodric House, 5 Boldero Road Bury St. Edmunds Suffolk. IP32 7BS

Tel: 01767 677445 admin@chaucersolutions.co.uk www.chaucersolutions.co.uk

Authorisations (Title VII Regulation 1907/2006): No specific authorisations are known for this product.

Restrictions (Title VIII Regulation 1907/2006): No specific restrictions on use are known for this product.

16. OTHER INFORMATION

Full text of H – Statements referred to under sections 2 and 3

- H225: Highly flammable liquid and vapour
- H301: Toxic if swallowed
- H302: Harmful if swallowed
- H311: Toxic in contact with skin
- H319: Causes serious eye irritation
- H331: Toxic if inhaled
- H370: Causes damage to organs
- H371: May cause damage to organs

Full text of P – Statements referred to under sections 2

- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P233: Keep container tightly closed
- P243: Take precautionary measures against static discharge
- P260: Do not breathe dust / fumes / gas / mist / vapours / spray
- P264: Wash hands thoroughly after handling
- P270: Do not eat, drink or smoke when using this product
- P271: Use only outdoors or in a well-ventilated area
- P280: Wear protective gloves / protective clothing/eye protection/face protection
- P303+P361+P353:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water P304+P340:

IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing P305+P351+P338:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

- P312: Call a POISON CENTER / doctor / medical professional / if you feel unwell
- P330: Rinse mouth
- P337+313:
 - If eye irritation persists get medical advice/attention
- P370+378:

In case of fire: Use appropriate fire extinguisher for extinction.

P403+233:

Store in a well-ventilated place. Keep container tightly closed

- P403+235:
 - Store in a well-ventilated place. Keep cool
- *P501: Dispose of contents / container to a waste management service provider, according to the local law and regulations*

Further information:

According to Regulation (EC) No. 1907/2006 the information in this safety data sheet is based on the properties of the material known to Chaucer Solutions Ltd at the time the data sheet was issued. The Safety data sheet is intended to provide information for a health and safety assessment of the material and the circumstances, under which it is packaged, stored or applied in the workplace. The information hereon is reliable to the best of our knowledge. However, the recommendations or suggestions hereon shall not be construed as a warranty or representation as to the results, safety and efficacy. Users should always make their own evaluations and tests suitable for their particular needs. We cannot be held liable for any loss or damage arising from the use of the information hereon. This document is not intended for quality assurance purposes.

- End of Safety Data Sheet -

Page 9 of 9